

1/3" SONY Exview HAD II CCD, 650 TV Lines

FEATURE

- 1/3" Sony Exview HAD II CCD
- Sony Effio-E 650 TVL
- Build-in 23 PCS IR LED & 1EA Sensor
- Metal Design, Water-Proof Camera
- DC 12V Power Supply



IR DOME CAMERA



SPECIFICATIONS

Model No	TC-628A
Image Sensor	1/3" Exview HAD II CCD
Total Pixel	PAL : 960H*582V
Horizontal Resolution	650 TVL
Min. Illumination	0 Lux IR on
S/N Ratio	≥52dB
Video Output	CVBS : 1.0Vp-p/75Ω Composite
Gamma Correction	0.45
Frequency	H:15.734 KHz / V:15.625KHz / V:50Hz
Sync. System	Internal Synchronization
Electronic Shutter	1/50 -1/100,000 SEC
Scanning System	2:1 Interlace
White Balance	AUTO
Backlight Compensation	AUTO
A.G.C	AUTO
Exposure Mode	EE
On Screen Display	None
ATR	AUTO
Noise Reduction	2D-NR
IR LED	Build-in 23 PCS IR LED & 1EA Sensor
IR View Distance	20 m.
Lens Type	Build-in
Power Supply	DC12V±5%
Power Consumption	≤2W
Work Humidity	≤85%RH
Operation Temperature	-10°C ~+50°C
External Case	Aluminum Alloy (Vandal Resistant IP66)